

Hoses

PA12 HL & PA12 HL FLEXIBLE HOSES (DIN 73378)



Partnr	Omschrijving	D2	S	D1	Working pressure	Vetgevuld	Packing unit
0620-0004-0403	PA12 HL FLEXIBLE	4	0,85	2,3	36 BAR	Empty	100M
0620-0004-0404	PA12 HL	4	0,85	2,3	61 BAR	Empty	100M
0620-0004-0602	PA12 HL	6	1.5	3	93 BAR	Empty	50M
0620-0004-0603	PA12 HL	6	1.5	3	93 BAR	Empty	100M
0620-0004-0605	PA12 HL	6	1.5	3	93 BAR	Empty	500M
0620-0007-0603	PA12 HL FLEXIBLE	6	1.5	3	82 BAR	Empty	100M
0620-0007-0605	PA12 HL FLEXIBLE	6	1.5	3	82 BAR	Empty	500M
0620-0005-0604	PA12 HL	6	1.5	3	93 BAR	Filled NLGI 00	50M
0620-0005-0603	PA12 HL	6	1.5	3	93 BAR	Filled NLGI 00	100M
0620-0009-0603	PA12 HL FLEXIBLE	6	1.5	3	82 BAR	Filled NLGI 00	100M

Application

This hose is used for Lubrication applications for Industrial, hand held or automatic (centralized) grease lubrication systems.

Grease filled

If desired, we can fill these lubrication hoses with NLGI 2 grease. This will save you a lot of time during the assembly of the hoses!

PDF specification sheets:

[Technical specification sheet PA12 HL PHL tubes unfilled](#)

[Technical specification sheet PA12 HL PHL tubes grease filled](#)