

Industrial Hoses

PVC SUCTION/DISCHARGE HOSE FLEXIBEL



<i>Inside diameter</i>	<i>Thickness</i>	<i>Working pressure</i>	<i>Vacuum</i>	<i>Bending radius</i>	<i>Roll length</i>
10mm	3mm	7 bar	0,8 bar	20mm	60m
12mm	3mm	7 bar	0,8 bar	25mm	60m
14mm	3,2mm	6 bar	0,8 bar	30mm	60m
16mm	3,2mm	6 bar	0,8 bar	35mm	60m
18mm	3,2mm	6 bar	0,8 bar	40mm	60m
20mm	3,5mm	5 bar	0,8 bar	50mm	60m
22mm	3,5mm	5 bar	0,8 bar	55mm	60m
25mm	4mm	5 bar	0,8 bar	75mm	60m
30mm	4,2mm	4,5 bar	0,8 bar	90mm	60m
32mm	4,2mm	4,5 bar	0,8 bar	95mm	60m
35mm	4,5mm	4 bar	0,8 bar	105mm	60m
38mm	4,5mm	4 bar	0,8 bar	115mm	30m
40mm	4,5mm	3 bar	0,8 bar	120mm	30m
45mm	5mm	3 bar	0,8 bar	135mm	30m
51mm	5mm	3 bar	0,8 bar	150mm	30m
60mm	6mm	2,5 bar	0,7 bar	180mm	30m
63mm	6mm	2,5 bar	0,7 bar	190mm	30m
70mm	6,5mm	2 bar	0,7 bar	210mm	30m
76mm	7mm	2 bar	0,7 bar	225mm	30m
80mm	7mm	2 bar	0,7 bar	240mm	30m
90mm	7mm	2 bar	0,6 bar	270mm	30m

Inside diameter

102mm

Thickness

7mm

Working pressure

2 bar

Vacuum

0,6 bar

Bending radius

300mm

Roll length

30m

PVC hose with steel spiral

Norm: REG(EU) 10/2011 Class A,B,C,D1

Temp: -10°C + 60°C

Transparent smooth PVC hose, phthalate free

Reinforcement: steel spiral

Cover: transparent PVC - most chemical and weather resistant